



The pump is a submersible drainage pump fitted with noryl impellers and stainless steel strainer. The pump has can handle particles up to 3mm.

The pump is characterised by:

- Glass filled pump body and noryl impellers for durability
- Fully automatic operation.
- Dual mechanical seals (Carbon ceramic on pump side and silicon carbide/ceramic in oil bath on motor side)
- Carry handle for ease of transport
- 240V single phase motor with in-built auto reset thermal overload.
- 10m of power cable.
- Dewatering of cellars, garages etc.
- Pumping clean or slightly dirty water
- Flows to 105L/min
- Heads to 32 m

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	550W
Current:	4.0 amps
Capacitor:	20 uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	F
Power cable length:	10 m H07RNF
Net weight:	12 kg
Dimensions:	171Lx162Wx461H (mm)

12 Month Bianco Pumpz Warranty

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

Pump body:	Glass filled nylon
Strainer:	304 SS
Impeller:	Glass filled nylon
Shaft:	Stainless Steel 410
Shaft seal:	Dual mechanical seals (Carbon ceramic on pump side and silicon carbide/ceramic in oil bath on motor side)

Installation:

Maximum ambient temperature:	40 °C
Pipe connections discharge:	1 1/4" F

